

BESS Module 46 kWh

Liquid-cooled BESS module based on prismatic LFP cells



Liquid-cooled BESS module based on HiTHIUM prismatic LFP BESS Cell 300 Ah with very high cyclic lifetime.

Specially optimised for use in stationary battery storage systems with the highest requirements on safety, reliability and performance. Suitable e.g. for I&C, utility applications.

- Product certifications: IEC 62619 (cell level), UL 1973, UL 9540A, UN 38.3
- Company certifications:ISO 9001, ISO 14001, ISO 45001
- Environmental Compliance: ROHS, REACH

High safety

- Based on HiTHIUM BESS 300 Ah prismatic LFP cell with high thermal stability
- High thermal stability thanks to liquid cooling

Low LCOS (Levelised Cost of Storage)

- Very long cycle life thanks to advanced material and process technologies
- Excellent thermal management improves energy throughput by ensuring optimal operating temperature

BESS Module 46 kWh

Liquid-cooled BESS module based on prismatic LFP cells with high cyclic lifetime



| GENERAL | |
|------------------------------|--------------------------|
| Cell Type | HiTHIUM LFP71173207 |
| Cell Capacity | 300 Ah ^{1,2} |
| Battery Configuration | 1P48S |
| Cooling Method | Liquid Cooling |
| Coolant | 50 % Water / 50 % Glycol |
| Gravimetric | > 139 Wh/kg |
| Volumetric | > 210 Wh/l |
| Туре | LFP300-1P48S |
| Application Altitude | ≤ 4,000 m |

| ELECTRICAL | |
|---------------------------------|----------------------------|
| Nominal Voltage | 153.6 V |
| Operating Voltage | T > 0 °C 120 175.2 V |
| | T ≤ 0 °C 96 175.2 V |
| Nominal Energy | 46.1 kWh ^{1,2} |
| Nominal SOC at delivery | 27 % ² |
| Nom. Charge / Discharge Rate | 0.5 P / 0.5 P ² |

| MECHANICAL | |
|------------------------|----------------------|
| Dimensions (L x W x H) | 820 x 1,150 x 245 mm |
| Weight | 340 kg |
| Protection Level | IP 67 |

| TEMPERATURE RANGE | |
|-----------------------|---------------------------|
| Operating | -30 °C 50 °C ³ |
| Storing (recommended) | -20 °C 35 °C ³ |

| PRODUCT CERTIFICATIONS | |
|--------------------------|---|
| Certificates and Reports | IEC 62619 (cell level), UL 1973, UL 9540A, UN 38.3 |

| ENVIRONMENTAL | |
|---------------|-------------|
| Compliance | ROHS, REACH |
| | Cobalt free |

| COMPANY CERTIFICATIONS | | |
|------------------------|--------------------------------|--|
| | ISO 9001, ISO 14001, ISO 45001 | |

HiTHIUM Energy Storage Technology USA Inc.

Address: 4046 Clipper Ct, Fremont, CA 94538, United States Email: hithium@hithium.com

Xiamen HiTHIUM Energy Storage Technology Co., Ltd.

Address: HiTHIUM Industrial Park, Tongxiang High-Tech Zone, Xiamen, Fujian, China | Email: hithium@hithium.com





¹ 0.5 P / 0.5 P

² 25 °C +/- 2.0

³ ambient temperature