

ESS **Cell** 314 Ah

Prismatic LFP cell optimised for use
in stationary ESS



Prismatic LFP cell with very high cyclic lifetime and improved safety characteristics.

Specially optimised for use in stationary battery storage systems with the highest requirements on safety, reliability and performance. Suitable e.g. for industrial, utility, and grid serving applications.

- Product certifications:
IEC 62619, UL 9540A, UL 1973, GB/T 36276, UN 38.3
- Company certifications:
ISO 9001, ISO 14001, ISO 45001, SA 8000
- Environmental Compliance:
RoHS, REACH, Regulation (EU) 2023/1542, Cobalt free

High safety

- HiTHIUM-developed prismatic LFP cell with high thermal stability.
- No fire or explosion during nail penetration and crush tests
- Ultra wide operating temperature range

Low LCOS (Levelised Cost of Storage)

- Very high cyclic lifetime $\geq 13,000$ cycles, thanks to advanced material and process technologies

Flexible and versatile use

ESS Cell 314 Ah

Prismatic LFP cell optimised for use in stationary ESS



GENERAL

Nominal Capacity	314 Ah ^{1,2}
Nominal Energy	1,004.8 Wh ^{1,2}
Cell Chemistry	LiFePO ₄ (LFP)
Nominal Cycles	≥ 13,000 ^{1,2,3}
Gravimetric ED	≥ 173.2 Wh/kg
Volumetric ED	≥ 382.6 Wh/L
Cell Model	LFP71173207/314Ah

ELECTRICAL

Nominal Voltage	3.2 V ^{1,2}
Operating Voltage	T > 0°C 2.50 ... 3.65 V T ≤ 0°C 2.00 ... 3.65 V
AC Resistance (1 kHz)	0.20 mΩ +/- 0.05 ⁴
Max. Self-discharge Rate	3 %/month ^{2,4}
Nominal Continuous Charge Rate	0.5 P
Nominal Continuous Discharge Rate	0.5 P

¹ 0.5 P / 0.5 P

² 25°C +/- 2.0

³ 65 % SOH

⁴ 27 % SOC

MECHANICAL

Dimensions (L x W x H)	174.70 x 71.70 x 207.11 mm
Type	Prismatic
Weight	5.60 kg +/- 0.2
Volume	2.59 L

TEMPERATURE RANGE

Charging	0°C ... 60°C
Discharging	-30°C ... 60°C
Storing (Recommended)	-20°C ... 35°C

PRODUCT CERTIFICATIONS

Safety Certificates	IEC 62619, UL 9540A, UL 1973 GB/T 36276
Safe Transportation	UN 38.3

ENVIRONMENTAL

Compliance	RoHS, REACH, Cobalt free
Battery Regulation (EU)	2023/1542

COMPANY CERTIFICATIONS

ISO 9001, ISO 14001,
ISO 45001, SA 8000

HiTHIUM Energy Storage Technology USA Inc.

Address: 4046 Clipper Ct, Fremont, CA 94538, United States
Email: hithium@hithium.com

Xiamen HiTHIUM Energy Storage Technology Co., Ltd.

Address: HiTHIUM Industrial Park, Tongxiang High Tech Zone,
Xiamen, Fujian, China | Email: hithium@hithium.com



LinkedIn



Website