

∞ Power

6,922 MWh

Liquid-cooled energy storage system



Preliminary

Liquid-cooled energy storage system based on HiTHIUM prismatic LFP ESS Cells 1300 Ah with high cyclic lifetime.

Improved safety characteristics and specially optimised for the highest requirements on safety, reliability and performance. Suitable for industrial, utility, and grid serving applications.

- Product certifications and compliance*: IEC 62619, IEC 62477, IEC 63056, IEC 61000, IEC 62933, UL 1973, UL 9540A, UL 9540, NFPA 855, UN 38.3
- Company certifications: ISO 9001, ISO 14001, ISO 45001, SA 8000
- Environmental compliance*: RoHS, REACH, Cobalt free
- Eco-friendly: Low noise, new type of eco-friendly refrigerant, high recyclability.
- Flexible solution: String or central PCS compatible.

High safety

- High thermal stability thanks to innovated liquid cooling design.
- Multi-stage, active fire detection and protection system, compliance to NFPA 855.
- 3-level BMS for cell and system monitoring and protection.

Low LCOS (Levelised Cost of Storage)

- High cyclic life and low auxiliary consumption due to excellent thermal management improve energy throughput by ensuring optimal operating temperature.
- Highly integrated: including thermal management system, fire protection system, BMS, etc.
- Supports back to back and side by side installations.

COPower

6,922 MWh

Liquid-cooled energy storage system based on prismatic LFP cells with very high cyclic lifetime



GENERAL

Configuration	4*1P416S
Cooling Method	Liquid Cooling
BMS Communication	CAN, RS485, Ethernet
Gravimetric ED	≥ 135 Wh/kg
Volumetric ED	≥ 160 Wh/L
Application Altitude	≤ 4.000 m

ELECTRICAL

Nominal Voltage	1.331,2 V
Operating Voltage	1.100 ... 1.500V
Nominal Energy	6.922 kWh ^{1,2}
Nominal SOC at Delivery	27 % ²
Nominal Charge/Discharge Rate	0,125 P / 0,125P
Round Trip Efficiency	≥ 96 % ^{1,2}

¹ 0,125 P / 0,125 P

² 25 °C +/- 2 °C

³ ambient temperature

⁴ battery compartment

^{*} In progress

MECHANICAL

Dimensions (L x W x H)	6.058 x 2.438 x 2.896 mm
Maximum Weight	50.000 kg
Protection Level	IP 66 ⁴

TEMPERATURE RANGE

Operating	-30 °C ... 55 °C ³
Storing (Recommended)	-20 °C ... 35 °C ³

PRODUCT CERTIFICATIONS AND COMPLIANCE*

Certificates and Compliance	IEC 62619, IEC 62477, IEC 63056, IEC 61000, IEC 62933, UL 1973, UL 9540A, UL 9540, NFPA 855
Safe Transportation	UN 38.3

ENVIRONMENTAL*

Compliance	RoHS, REACH, Cobalt free
Regulation (EU)	2023/1542

COMPANY CERTIFICATIONS

ISO 9001, ISO 14001, ISO 45001, SA 8000

HiTHIUM Energy Storage Technology Deutschland GmbH

Website: <https://hithium.com> | Email: Contact@hithium.de

Address: Landsberger Str. 155, 80687 Munich, Germany

Xiamen HiTHIUM Energy Storage Technology Co., Ltd.

Address: HiTHIUM Industrial Park, Tongxiang High Tech Zone, Xiamen, Fujian, China | Email: hithium@hithium.com



LinkedIn



Website