

∞Power 1022kWh

Liquid-cooled battery storage system



The ∞Power 1022kWh cabinet is based on cutting-edge 1175Ah cells (4-hour), performing safety and reliability excellently while achieving ultimate cost efficiency.

Safety and Reliability

- Cluster-independent structure with fire insulation.
- Pack-built-in aerosol fire protection.
- Compliant with NFPA855-2026 certification.

Space Saving

- Only 3.4m² land occupation for single cabinet.
- 42.3% space saving for 6-units deployment compared with container.
- Modular design, supporting DC-side parallel expansion.

Ultimate Levelized LCOE

- Equipped with 1175Ah cells, reducing cell quantity by 70%.
- Cycle life over 8000 times at SOH ≥ 70%.
- Simplified wiring and commissioning.


High Usability

- 1000V DC system, adaptable to AC 400V and above power grids.
- Compatible with multiple PCS models, meeting grid-connection requirement by different countries.
- Built-in EMS for 24/7 system operation monitoring.

∞Power

1022 kWh

Liquid-cooled energy storage system based on prismatic LFP cells with very high cyclic life-time



GENERAL	
Battery Type	HiTHIUM LFP 1175Ah
Module Configuration	1P34S
Battery Modules	8
Cooling Method	Liquid cooling
Configuration	Serial connection
Communication Interface	CAN/RS485/Ethernet
Application Altitude	≤ 4000 m (>2000m derating)

ELECTRICAL	
Nominal Voltage (Cabinet)	870.4 V
Nominal Voltage (Module)	108.8 V
Operating Voltage Cabinet	707.2 V ... 992.8 V ¹
Nominal Energy Cabinet	1022.72 kWh ^{1,2,3}
Nominal Energy Module	127.84 kWh ^{2,3}
Nominal SOC at delivery	27% ³
Nominal Charge/Discharge Rate	0,25 P / 0,25 P

¹ 8 modules

² 0.25 P / 0.25 P

³ 25°C +/- 2,0

⁴ ambient temperature

MECHANICAL	
Dimensions (L x W x H)	1750 x 1950 x 2400 mm
Weight Cabinet	≤ 8000 kg ¹
Weight Battery Module	≤800±10 kg
Protection Level	IP 55
Corrosion Rating	C5M

TEMPERATURE RANGE	
Operating	-30 °C ... 55 °C ⁴ (>40°C reduction)
Storing (Recommended)	-20 °C ... 35 °C ⁴

SAFETY MEASURES	
Fire Alarm System	Smoke detector, heat detector
Fire Suppression Measures	Aerosol fire suppression system, Deflagration Vent, Ventilation, Fire Hose Coupling

HiTHIUM Energy Storage Technology Deutschland GmbH

Website: <https://hithium.com> | Email: Contact@hithium.de

Address: Landsberger Str. 155, 80687 Munich, Germany

Xiamen HiTHIUM Energy Storage Technology Co., Ltd.

Address: HiTHIUM Industrial Park, Tongxiang High Tech Zone, Xiamen, Fujian, China | Email: hithium@hithium.com



LinkedIn



Website